Indirect Lighting

Focal[™]

Solution Document

Featured SimpleSpec

600.01


Front Reception Lightbox



600.19 Geometric Lightbox




600.02 Wrapped Reception Lightbox



Introduction Focal Series

- . LED Life of approximately 50K hours, under normal operating conditions
- . Low wattage, low heat, low voltage (24VDC Operation)
- . Design prevents "scalloping" effect, providing consistent and uniform illumination
- . Emits no UV or infrared light and does not contain lead, mercury, or glass, allowing for eco-friendly handling and disposal when required
- . UL Listed. Conforms to UL Standard 8750 and/or 2108
- . Certified to CAN/CSA Standard 22.2 No. 250.0-04 or C22.2 No. 9
- . Available in Natural White (4500K)
- . 7W per foot
- . Suitable for Damp Locations IP65





Indirect Lighting

Focal[™]

Solution Document

Table of Contents

- 1 Specifications
- 2 SimpleSpec Solutions
 - 2 600.02.02 6 Sided Square Lightbox
- 3 Installation Diagrams
- 5 Dimensions





Specifications

LEDs

P	art Number	LED Bar Color	Size	Angle	Volts	Power (Watts)	Max Watts Per Run	Color Temperature
	3-60-775	Natural White	45"	20°×45°	24	25.2	96 W	4500 K
	3-60-776	Natural White	23.125"	20°×45°	24	12.6	96 W	4500 K
	3-60-777	Natural White	5.625"	20°×45°	24	2.52	96 W	4500 K



Focal Linear Light

Drivers

Part Number	Description	Dimensions	Input Voltage	Input Current	Output Power	Output Voltage	Output Current
3-60-497	0-10V Slide Control Wall Dimmer	-	-	_	-	-	-
3-60-765	96W Dimmable Power Supply	11.7"×2.36"×1.4"	120-277VAC	.8/.35	96	24	4







3-60-765 Dimmable Power Supply

Connectors

Part Number	Description
3-60-778	12" Wire Extension
3-60-779	48" Wire Extension
3-60-780	144" Wire Extension



Typical Wire Extension





Focal[™]

Solution 1

SimpleSpec 600.02.02

6 Sided Square Lightbox





Overall View

^{*}An optional dimmer is also available - see dimming wiring diagrams on pages 3 - 4.




^{*}See page 3 for wiring diagram


Focal[™]

Installation

Focal Series Wiring Diagram



Wiring Diagram - 0-10V Dimming ≤100W






Focal[™]

Installation

Wiring Diagram - 0-10V Dimming 100W-1200W







Dimensions

3-60-765 - Dimmable Power Supply

12.1" (307.9mm)

7.4" (188.2mm)

11.7" (298mm)

1.4" (35mm)

